
weld
ILLUMINAZIONE LED

3 ANNI DI GARANZIA


VITA UTILE 35.000 h | IP40 | IK06

ATLAS RG30CS




Colore di luce:
Regolabile con selettore





FOTOMETRIE



120°

Peso: 0.2 Kg

Caratteristiche Elettriche

Tensione:	220 - 240 V
Frequenza:	50 - 60 Hz
Potenza:	4W
Corrente LED:	300 mA
Fattore di potenza:	≥0.90
Classe di isolamento:	Classe II (Classe I su richiesta)
Temperatura di esercizio:	-20 / + 40 °C

Specifiche chip LED

Tipo LED:	SMD 2835
Numero LED:	20
Colore luce:	Regolabile con selettore
Vita utile :	> 35.000 h corrente modulo LED 600mA (Ta25°)

Caratteristiche emissione

Flusso luminoso:	480 Lm
Angolo di diffusione:	120°
Resa cromatica:	CRI ≥ 80

Protezioni

Grado di protezione lampada:	IP40
Grado di protezione driver:	IP20
Protezione agli urti:	IK06

Caratteristiche meccaniche

Materiale corpo lampada:	PC
Tipo diffusore:	PC OPALE
Colore:	Bianco

Conformità e certificazioni componentistica

EN 60598-1:2008/A11:2009: Luminaires – General requirements and tests. **EN 60598-2-5:1998:**Luminaires – Particular requirements. **EN 62471:**Photo biological safety of lamps and lamp systems. **EN 62493:2010:**Asses sment of lighting equipment related to human exposure to electromagnetic fields.
EN 55015:2006/A1:2007/A2:2009: Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment. Equipment for general lighting purposes – EMC requirements. **EN 61547:2009:** Limits for Harmonic emissions (<16A per phase). **EN 61000-3-2:2006/A1:2009/A2:2009/ EN 61000-3-3:2008:** Limits. (Limitation of voltage changes, voltage fluctuations and flicker in public low voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection)

VITA UTILE 35.000 h | IP40 | IK06

WELD ILLUMINAZIONE SRL – C.da Colamazza snc, 89900 Vibo Valentia (VV) – Tel. 0963-70402Mail: info@weldilluminazione.it – Web: WWW.WELDILLUMINAZIONE.IT